CONSTANT FORCE SOCKET

BACKGROUND OF THE INVENTION

1. Field of the Invention

The present invention relates generally to a socket for use with a wrench or the like to turn bolts and nuts, and more particularly, to a constant force socket, which enables the user to apply a constant torsional force to the workpiece.

2. Description of the Related Art

Regular torsion tools include two types, namely, the conventional mechanical types and the electronic types. These two different types of torsion tools have different prices and are for different applications. Regular sockets for use with torsion tools do not provide an applied force or torsional force control function. Ease of use is the only function of conventional sockets. When in use, a socket works as an adapter between the torsion tool (wrench or power hand tool) and the workpiece (screw bolt or not). During use, the control and maintenance of applied force are completely decided by the user. However, it is difficult to get the information of the margin of safety of every product from the assembly line. An electronic torsion tool (for example, an electronic wrench) can only measure the amount of force applied at each time. It cannot control the amount of applied force, or keep the applied force within a constant range.

A conventional socket is to be sued with a torsion tool to lock/unlock a bolt or nut. However, the locking force is determined subject to the user's feeling. Excessively high locking force may cause damage to the workpiece. Insufficient locking force cannot lock the workpiece positively.

FIG. 1 shows a conventional socket for use with a torsion tool to turn a bolt

or nut. This structure of socket may be made in different sizes to fit different bolts and nuts. However, this structure of socket cannot control the applied torsional force.

SUMMARY OF THE INVENTION

The present invention has been accomplished under the circumstances in view. It is the main object of the present invention to provide a constant force socket, which enables the user to adjust apply a constant torsional force to the workpiece. It is another object of the present invention to provide a constant force socket, which enables the user to adjust the set torsional force.

To achieve these and other objects of the present invention, the constant force socket comprises a socket body, the socket body having an inner hole axially extended to one end thereof and a set of teeth radially disposed around the border inside the inner hole; a ratchet wheel mounted in the inner hole inside the socket body, the ratchet wheel having a tool hole disposed at one side thereof and adapted to receive a torsion tool to be inserted into the inner hole of the socket body, and a set of teeth radially disposed at an opposite side thereof and adapted to engage the teeth of the socket body; a screw member threaded into the inner hole of the socket body; and spring means mounted in the inner hole inside the socket body and stopped between the screw member and the ratchet wheel to force the ratchet wheel into engagement with the teeth of the socket body. By means of rotating the screw member inwards/outwards in the inner hole of the socket body, the spring force of the spring means is adjusted, and therefore the set torsional force is relatively changed.

BRIEF DESCRIPTION OF THE DRAWINGS

FIG. 1 is an elevational view of a socket according to the prior art.

FIG. 2 is a sectional view of a constant force socket according to the present invention.

FIG. 3 is a left side view of the constant force socket according to the present invention.

FIG. 4 is a right side view of the constant force socket according to the present invention.

FIG. 5 is an elevational view of the socket body for the constant force socket according to the present invention.

FIG. 6 is a perspective view of the ratchet wheel for the constant force socket according to the present invention.

FIG. 6A is an enlarged view of part A of FIG. 6.

FIG. 7 is a schematic drawing showing the tooth form of the ratchet wheel for the constant force socket according to the present invention.

DETAILED DESCRIPTION OF THE INVENTION

Referring to FIG.S 2~4, a constant force socket in accordance with the present invention is shown comprised of a socket body **10**, a stepped ratchet wheel **20**, a spring member **30**, and a screw member **40**.

The socket body **10** is a hollow block having a coupling hole **11** axially extended to one end and adapted to receive a locating member (for example a screw nut or screw bolt), an inner hole **12** axially extended to the other end, a set of teeth **13** radially disposed at the inner side inside the inner hole **12** (see FIG. 5), and an inner thread **14** extended around the inside wall within the inner hole **12** near the outer side. The teeth **13** each have a first sidewall **131** and a second sidewall **132** respectively sloping at two sides at different angles for locking/unlocking control. Alternatively, the teeth **13** can be made having the respective first sidewall **131** to be a sloping wall and the respective second sidewall **132** to be a vertical wall.

The stepped ratchet wheel **20** is mounted inside the inner hole **12**, having an

axially extended tool hole **21** (see FIG. 6) adapted to receive a torsional tool, and a series of teeth **22** radially arranged along the periphery at one end (see FIGS. 6 and 6A). The teeth **22** each have a first sidewall **221** and a second sidewall **222** respectively sloping at two sides at different angles for locking/unlocking control. Alternatively, the teeth **22** can be made having the respective first sidewall **221** to be a sloping wall for locking control and the respective second sidewall **222** to be a vertical wall for unlocking control (see FIG. 7). After engagement between the teeth **22** of the stepped ratchet wheel **20** and the teeth **13** of the socket body **10**, the constant force socket can be driven to lock/unlock the workpiece, for example, a screw bolt or the like. When locked, the teeth **22** of the stepped ratchet wheel **20** and the teeth **13** of the socket body **10** trip out automatically.

The spring member **30** is a compression spring received inside the inner hole **12** and sleeved onto the stepped ratchet wheel **20**, having one end stopped against the ratchet wheel **20** and the other end. The spring member **30** forces the stepped ratchet wheel **20** into engagement with the teeth **13** of the socket body **10**, enabling the teeth **22** of the stepped ratchet wheel **20** and the teeth **13** of the socket body **10** to trip out automatically after the workpiece (screw bolt or nut) has been locked. The positioning of the spring member **30** is not limited to the aforesaid arrangement, i.e., the spring member **30** can be set in any of a variety of positions that achieve the same effect.

The screw member **40** is a hollow member stopped against the other end of the spring member **30**, having an outer thread **41** extended around the periphery and threaded into the inner thread **14** of the socket body **10**. By means of rotating the screw member **40** inwards or outwards in the inner hole **12**, the spring force of the spring member **30** is relatively adjusted. Therefore, the screw member **40** has two functions, one to hold down the parts of the constant force socket, and the other to adjust the

torsion. After adjustment of the screw member **40**, the screw member **40** may be welded to the socket body **10**, or locked to the socket body **10** by lock means (not shown). Alternatively, the screw member **40** can movably be threaded into the inner thread **14** inside the inner hole **12** of the socket body **10** without locking for convenient adjustment.

When assembled, the teeth **22** of the stepped ratchet wheel **20** are meshed with the teeth **13** of the socket body **10** for transmission of rotary driving force, and the spring member **30** is stopped between the screw member **40** and the ratchet wheel **20** to keep the ratchet wheel **20** in engagement with the teeth **13**. When in use, the coupling hole **11** of the socket body **1** can be attached to any of a variety of screw bolts and nuts, and the tool hole **21** of the ratchet wheel **20** can receive a torsion tool for turning the constant force socket and the workpiece to which the coupling hole **11** of the socket body **1** is attached. The spring member **30** holds down the ratchet wheel **30** in engagement with the teeth **13** of the socket body **10**, and gives a room for enabling the ratchet wheel **20** to trip out when the applied force surpassed the set torsion during working.

If the applied force surpassed the set torsional force when locking the workpiece (screw bolt or nut) with a torsion tool, the teeth **13** and **22** will automatically trip out along the first sidewalls **131** and **221**, and then the teeth **22** will be forced into engagement with the teeth **13** again by the spring member **30** after the ratchet wheel **20** has been biased through an angle. Further, the engagement between second sidewalls **132** and **222** prevents trip-out of the ratchet wheel **20** from the socket body **10** when rotated in the reversed direction to loosen the workpiece (screw bolt or not).

As indicated above, if the applied force surpassed the set torsional force of the constant force socket when locking the workpiece (screw bolt or nut), the constant

force trips out automatically to run idle, preventing damage to the constant force socket. When loosening the workpiece (screw bolt or not), the constant force socket is prohibited from tripping out, and can be driven to loosen the workpiece (screw bolt or nut) directly and positively.

It is not requisite to use the constant force socket with an electronic torsion tool (for example, an electronic wrench). Without an electronic torsion tool, the invention achieves torsion control. The constant force socket of the present invention is practical for use in any of a variety of industries including machinery industry, automobile industries, electronic equipment industry, food equipment industry, and etc., to lock or unlock screw bolts and nuts.

As indicated above, after installation of the screw member **40**, the spring member **30** and the ratchet wheel **20** in the socket body **10**, the acceptable torsional force of the socket is set. When locking the workpiece (screw bolt or nut), the maximum torsional force is transmitted through the constant force socket to the workpiece. When unlocking the workpiece, the ratchet wheel does not trip out, and the torsional force is positively transmitted to the workpiece, causing the workpiece to be accurately unlocked (loosened).

Although a particular embodiment of the invention has been described in detail for purposes of illustration, various modifications and enhancements may be made without departing from the spirit and scope of the invention. Accordingly, the invention is not to be limited except as by the appended claims.